

Technical Specifications

- Type** : 2-Way Bookshelf
- **LF Driver** : 5 1/4 inch magnetically shield mineral filled polypropylene curved cone with high temperature voice coil and damped rubber surround.
- HF Driver** : 1 inch magnetically shield natural Silk Dome.
- **Frequency Response** : 33Hz - 22kHz
- **Crossover Frequency** : 2.7kHz
- **LF Amplifier Power** : 40W
- HF Amplifier Power** : 30W
- S/N Ratio** : > 100dB below full output, 20kHz Bandwidth
- Input Connectors** : 1 x XLR Balanced Input Connector
1 x TRS Balanced/ Unbalanced Input Connector
- Polarity** : Positive signal at + input produce outward LF cone displacement
- **Input Impedance** : 20k ohms balanced, 10k ohms unbalanced
- **Input Sensitivity** : 200 mV input produces full output with Volume control at maximum.
- **Protection** : RF interference, output current limiting, over temperature, turn-on/off transient, subsonic filter, external mains fuse.
- Indicator** : Power ON/OFF indicator on rear panel
- Power Requirements**: Factory programmed for either 115V ~50/60Hz,
230V~50/60Hz or 100V~50/60Hz;
Power via detachable 3 circuit line cord.
- Cabinet**: vinyl laminated MDF
- Dimension** : 250 mm(H) x 166 mm(W) x 200 mm(D)
- Weight** : 5.0 kg/unit (without packing)

Remarks: Above specifications are subject to change without notice.